MANADO

財團法人金屬工業研究發展中心 機械測試實驗室

40768 台中市工業區 37 路 25 號 TEL: (04)23502169

Metal Industries Research & Development Centre Mechanical Testing Laboratory

No.25, 37th Road, Industrial Park, Taichung City 40768, Taiwan (R.O.C.)



Testing Laboratory 0099

Date: 2022/09/13

Accreditation No.: 111TD0913-271-C01

Certificate of Conformance for Freight Container Mechanical Seal Testing Seal Classification: High Security Seal

Customer:

Mega Fortris (Malaysia) Sdn. Bhd.

29, Jalan Anggerik Mokara 31/47, Kota Kemuning, Seksyen 31, 40460 Shan Alam, Selangor, Malaysia

Name of Article: High Security Seal

Type: MEGALOCK (ML) Serial No.: 000061~000086

Specification No. : ISO 17712:2013(E) Test Dates : 2022/08/30~2022/09/13

MIRDC, Certifies that 26 samples, 5 for each test and 1 for measurements, of the seal reference above were subjected to the following tests.

Test Item	Section Number	Classification
Evidence of Tampering (Minimum Diameter)	4.1.3	Pass
Tensile Test	5.2	High security seal (H)
Shear Test	5.3	High security seal (H)
Bending Test	5.4	High security seal (H)
Impact Test room temp	5.5	High security seal (H)
Impact Test reduced temp	5.5	High security seal (H)

Remarks: As per ISO17712:2013(E) Clause 5.1.2 "Testing is to be done once every two years".


Therefore, this report expires two years from the test completion date.

Results: The above listed tests were completed with no discrepancies noted. Refer to test report

number L0830271-T01 for complete details.

The test results contained herein pertain only to the specimens listed in this report. This report shall not be reproduced, except in full, without the written approval of MIRDC

Approved Signatory: CHIANG, Ching-Liu	青江
Engineer: SU, Yuan-Da	Chiang Chang liss 原語
	Su. Yuan-Da





40768 台中市工業區 37 路 25 號 TEL: (04)23502169

Metal Industries Research & Development Centre **Mechanical Testing Laboratory**

No.25, 37th Road, Industrial Park, Taichung City 40768, Taiwan (R.O.C.) 試驗報告 TEST REPORT



Test Report No.: L0830271-T01

Page 1 of 10

Customer:

Mega Fortris (Malaysia) Sdn. Bhd.

29, Jalan Anggerik Mokara 31/47, Kota Kemuning, Seksyen 31, 40460 Shan Alam, Selangor,

Malaysia

SUBJECT: Freight containers Mechanical seals classification Testing

Name of Article: High Security Seal

Type: MEGALOCK (ML) Received Date: 2022/08/30

Test Dates: 2022/08/30~2022/09/13

Date Issued: 2022/09/13

Chiang Ching lin CHIANG, Ching-Liu

報告簽署人 (Report Authorized Person)

Su. Yuan-Da SU, Yuan-Da

檢驗員 (Inspector)

Note: (1) The operation and testing of MIRDC laboratory are in conformity to the requirements of ISO/IEC 17025: 2017 (Taiwan Accreditation Foundation, Accreditation No.: 0099)

- (2) This report is responsible for designated samples only.
- (3) Reproduction of all or parts this report without a written approval is strictly prohibited.
- (4) Decision rules of conformance statement of this test report, do not consider uncertainty of measurement.



40768 台中市工業區 37 路 25 號 TEL: (04)23502169 Metal Industries Research & Development Centre

Mechanical Testing Laboratory

No.25, 37th Road, Industrial Park, Taichung City 40768, Taiwan (R.O.C.) 試驗報告 TEST REPORT



Test Report No.: L0830271-T01

Page 2 of 10

1. ABSTRACT

Customer:

Mega Fortris (Malaysia) Sdn. Bhd.

29, Jalan Anggerik Mokara 31/47, Kota Kemuning, Seksyen 31, 40460 Shan Alam, Selangor, Malaysia

Name of Article: High Security Seal

Type: MEGALOCK (ML)

Serial No.: 000061~000086

Quantity Tested: 26

Inspection Reference: ISO 17712:2013(E)

Test Item	Section Number	Serial No.	Results
Evidence of Tampering (Minimum Diameter)	4.1.3	000086	See Page 3
Tensile Test	5.2	000061~000065	See Page 4
Shear Test	5.3	000066~000070	See Page 6
Bending Test	5.4	000071~000075	See Page 7
Impact Test room temp	5.5	000075~000080	See Page 8
Impact Test reduced temp	5.5	000081~000085	See Page 8



40768 台中市工業區 37 路 25 號 TEL: (04)23502169 Metal Industries Research & Development Centre

Mechanical Testing Laboratory

No.25, 37th Road, Industrial Park, Taichung City 40768, Taiwan (R.O.C.) 試驗報告 TEST REPORT



Test Report No.: L0830271-T01 Page 3 of 10

2. Evidence of tampering Test:

Ambient Temp. : 19°C ; 60% R.H.

Inspection Reference: ISO 17712:2013(E)

Result:

Evidence of tampering Section 4.1.3

Specimen No.	Measu	Pass/Fail	
000000	Pin Head	18.38	Pass
000086	Lock Body	18.15	Pass

Requirement:

The minimum diameter (or minimum widest cross-dimension) for the metal components of a bolt seal shall be 18 mm.



Pin Head



Lock Body



40768 台中市工業區 37 路 25 號 TEL: (04)23502169 Metal Industries Research & Development Centre

Metal Industries Research & Development Centre Mechanical Testing Laboratory

No.25, 37th Road, Industrial Park, Taichung City 40768, Taiwan (R.O.C.) 試驗報告 TEST REPORT



Test Report No.: L0830271-T01

Page 4 of 10

3. Tensile Test:

Testing Instrument: Universal Testing Machine (No.TG0103)

Ambient Temp.: 19°C; 60% R.H

Inspection Reference: ISO 17712:2013(E)

Result:

Tensile Test Section 5.2

The seal was gripped in a tensile machine and a pull force applied.

Specimen No.	Requirement Load to failure	Result kN	Seal classification
000061	10.0 kN: High security seal 2.27 kN: Security seal < 2.27 kN: Indicative seal	23.9	High security seal (H)
000062		22.9	High security seal (H)
000063		23.1	High security seal (H)
000064		21.9	High security seal (H)
000065		19.1	High security seal (H)



40768 台中市工業區 37 路 25 號 TEL: (04)23502169 Metal Industries Research & Development Centre Mechanical Testing Laboratory

No.25, 37th Road, Industrial Park, Taichung City 40768, Taiwan (R.O.C.) 試驗報告 TEST REPORT



Test Report No.: L0830271-T01

Page 5 of 10

Universal Testing Machine



Tensile Set up





40768 台中市工業區 37 路 25 號 TEL: (04)23502169

Metal Industries Research & Development Centre Mechanical Testing Laboratory

No.25, 37th Road, Industrial Park, Taichung City 40768, Taiwan (R.O.C.) 試驗報告 TEST REPORT



Test Report No.: L0830271-T01

Page 6 of 10

4. Shear Test

Testing Instrument: Universal Testing Machine (No.TG0103)

Ambient Temp. : 19°C ; 60% R.H.

Inspection Reference: ISO 17712:2013(E)

Result:

Shear Test Section 5.3

The seal was fixed in a universal testing machine to withstand cutting with shearing blades and a compressive load applied slowly until the seal is severed.

Specimen No.	Requirement Load to failure	Result kN	Seal classification
000066	3.336 kN: High security seal 2.224 kN: Security seal <2.224 kN: Indicative seal	8.896	High security seal (H)
000067		8.896	High security seal (H)
000068		8.896	High security seal (H)
000069		8.896	High security seal (H)
000070		8.896	High security seal (H)

Shear Set up



SAFETY PRECAUTIONS - Do not exceed a shear force greater than 8900N(2001lbf). If the specimen has not failed at that force, halt the test and unload the test equipment. Record a shear force of 8896N (2000 lbf). Sudden and violent rupture of the test specimen can endanger personnel, equipment and property.



40768 台中市工業區 37 路 25 號 TEL: (04)23502169

Metal Industries Research & Development Centre Mechanical Testing Laboratory

No.25, 37th Road, Industrial Park, Taichung City 40768, Taiwan (R.O.C.) 試驗報告 TEST REPORT



Test Report No.: L0830271-T01

Page 7 of 10

5. Bending Test

Testing Instrument: FORCE GAURE Ambient Temp.: 19°C; 60% R.H

Inspection Reference: ISO 17712:2013(E)


Result:

Bending Test Section 5.4

Fix the locking end on the universal testing machine in a horizontal position.

Apply a load on the remaining portion of the seal at a distance (the moment arm) above the fixed end so as to bend the seal 90 degrees.

Specimen No.	Requirement Bending moment to failure	Result Nm	Seal classification
000071		84.9	High security seal (H)
000072	50 Nm: High security seal	83.5	High security seal (H)
000073	22 Nm: Security seal < 22 Nm: Indicative seal	83.4	High security seal (H)
000074		88.1	High security seal (H)
000075		83.2	High security seal (H)



Bend Set up



40768 台中市工業區 37 路 25 號 TEL: (04)23502169 Metal Industries Research & Development Centre

Mechanical Testing Laboratory No.25, 37th Road, Industrial Park, Taichung City 40768, Taiwan (R.O.C.) 試驗報告 TEST REPORT SSI/BISSENT OF STILL OF MENT OF MENT

Test Report No.: L0830271-T01

Page 8 of 10

6. Impact Test

Testing Instrument:

1. Impact Tester

2. Programmable Low Temp. Tester (No.SG5501)

Inspection Reference: ISO 17712:2013(E)

Impact Test Section 5.5

The impact test is performed at 18 degrees C and minus 27 degrees C of temperature. The impact load is applied at the locking mechanism of the seal in the direction opposite the direction used in locking the seal.

Result:

Impact Test at	Impact Test at 18 ℃					
Specimen No.	Requirement	Result Joule			Seal classification	
		13.56	27.12	40.68		
000076	40.68J: High security seal 27.12J: Security seal <27.12J: Indicative seal 5 impacts at each load	Pass	Pass	Pass	High security seal (H)	
000077		Pass	Pass	Pass	High security seal (H)	
000078		Pass	Pass	Pass	High security seal (H)	
000079		Pass	Pass	Pass	High security seal (H)	
000080		Pass	Pass	Pass	High security seal (H)	

Impact Test	Impact Test at -27 °C					
Specimen No.	Requirement	Result Joule			Seal classification	
		13.56	27.12	40.68		
000081	40.68J: High security seal 27.12J: Security seal <27.12J: Indicative seal 5 impacts at each load	Pass	Pass	Pass	High security seal (H)	
000082		Pass	Pass	Pass	High security seal (H)	
000083		Pass	Pass	Pass	High security seal (H)	
000084		Pass	Pass	Pass	High security seal (H)	
000085		Pass	Pass	Pass	High security seal (H)	



財團法人金屬工業研究發展中心 機械測試實驗室 40768台中市工業區 37路 25號 TEL: (04)23502169

40768 台中市工業區 37 路 25 號 TEL: (04)23502169 Metal Industries Research & Development Centre Mechanical Testing Laboratory

No.25, 37th Road, Industrial Park, Taichung City 40768, Taiwan (R.O.C.) 試驗報告 TEST REPORT SSING A DOCKER OF THE STATE OF

Test Report No.: L0830271-T01 Page 9 of 10



Impact Set up




40768 台中市工業區 37 路 25 號 TEL: (04)23502169 Metal Industries Research & Development Centre Mechanical Testing Laboratory

No.25, 37th Road, Industrial Park, Taichung City 40768, Taiwan (R.O.C.) 試驗報告 TEST REPORT



Test Report No. L0830271-T01

Page 10 of 10



Name of Article: High Security Seal Type: MEGALOCK (ML)

---End---